

TECHNICAL DATA SHEET

Straight suspension for CD profile 60/27 DAH 0600 SPECIAL

BRIEF CHARACTERISTICS:

The straight hinge is used as an anchor for the direct attachment of plasterboard profiles to the construction of buildings. It is produced in thicknesses of 0.80 and 1.00mm. Hinges make it easy to reduce the ceiling.



TECHNICAL DATA:

	Straight sus. DAH 0600 SPECIAL
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m ² exposure class B
length	120 mm
width	30 mm
weight	0,0346 kg/pcs
small package	100 pcs
large package	15 300 pcs/PAL
reaction to fire	class A1
load	0,40 kN



	Straight sus. DAH 0600 SPECIAL
thickness of material	0,9 mm
material	DX51
coating	galvanizing 100 g/m ² exposure class B
length	200 mm
width	30 mm
weight	0,0483 kg/pcs
small package	100 pcs
large package	9900 pcs/PAL
reaction to fire	class A1
load	0,40 kN

PULZ Myjava SK s.r.o., Čsl. armády 388/9, 907 01 Myjava,
IČO: 52961958, DIČ:2121252650,IČ DPH: SK2121252650,
tel.: +42134 621 61 41, e-mail: pulzmyjava@pulzmyjava.sk, web: www.pulzmyjava.sk
Production/Warehouse: Turá Lúka 416, 907 03 Myjava