

## TECHNICAL SHEET OF THE PRODUCT

### Straight suspension for CD profile 60/27 DAH 0600

#### Brief characteristics

The straight hinge is used as an anchor for the direct attachment of plasterboard profiles to the construction of buildings. It is produced in thicknesses of 0.80 and 1.00mm. Hinges make it easy to reduce the ceiling.

#### Technical data:

	<b>Straight sus. DAH 0600</b>
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m <sup>2</sup>
	exposure class B
length	<b>70 mm</b>
width	30 mm
weight	0,0346 kg/pcs
small package	100 pcs
large package	28 800 pcs/PAL
reaction to fire	class A1
load	0,40 kN



	<b>Straight sus. DAH 0600</b>
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m <sup>2</sup>
	exposure class B
length	<b>125 mm</b>
width	30 mm
weight	0,0483 kg/pcs
small package	100 pcs
large package	15 000 pcs/PAL
reaction to fire	class A1
load	0,40 kN



**Ing. Pavol Závodský – PULZ**  
ČSL armády 388/9  
907 01 Myjava  
**Place of business**  
Turá Lúka č.416  
Slovakia

**ID:** 11738286  
**VAT:** SK1020282252  
**GPS:**  
48.744167, 17.537133

**Tel:** +421 (0)34 621 61 41  
**Fax:** +421 (0)34 621 29 91  
**Mob:** +421 (0)949 175 845  
+421 (0)908 420 495  
**E-mail:** [pulzmyjava@pulzmyjava.sk](mailto:pulzmyjava@pulzmyjava.sk)  
**Web:** [www.pulzmyjava.sk](http://www.pulzmyjava.sk)

Accessories for plasterboard systems  
Suspended system for mineral ceiling "cassette ceiling"  
Accessories for ETICS and plasters



	<b>Straight sus. DAH 0600</b>
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m <sup>2</sup>
	exposure class B
length	<b>200 mm</b>
width	30 mm
weight	0,0680 kg/pcs
small package	100 pcs
large package	9 900 pcs/PAL
reaction to fire	class A1
load	0,40 kN



**Ing. Pavol Závodský – PULZ**  
ČSL armády 388/9  
907 01 Myjava  
**Place of business**  
Turá Lúka č.416  
Slovakia

**ID:** 11738286  
**VAT:** SK1020282252  
**GPS:**  
48.744167, 17.537133

**Tel:** +421 (0)34 621 61 41  
**Fax:** +421 (0)34 621 29 91  
**Mob:** +421 (0)949 175 845  
+421 (0)908 420 495  
**E-mail:** [pulzmyjava@pulzmyjava.sk](mailto:pulzmyjava@pulzmyjava.sk)  
**Web:** [www.pulzmyjava.sk](http://www.pulzmyjava.sk)