

TECHNICAL SHEET OF THE PRODUCT

Securing holder JSB

Brief characteristics

The securing holder JSB is used as an anchor element for the direct attachment of plasterboard profiles to the construction of buildings. It is manufactured in thicknesses of 0.90 mm. These JSB secure holders allow the ceiling to be easily lowered or anchored to the plasterboard wall.

Technical data:

	Securing holder JSB
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m ² exposure class B
length	50 mm
width	60 mm
weight	0,0297 kg/pcs
small package	100 pcs
large package	9 800 pcs/PAL
reaction to fire	class A1
load	0,40 kN



	Securing holder JSB
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m ²
	exposure class B
length	80 mm
width	60 mm
weight	0,0428 kg/pcs
small package	100 pcs
large package	7 000 pcs/PAL
reaction to fire	class A1
load	0,40 kN



	Securing holder JSB
thickness of material	0,8 mm
material	DX51
coating	galvanizing 100 g/m ²
	exposure class B
length	120 mm
width	60 mm
weight	0,0595 kg/pcs
small package	100 pcs
large package	7 000 pcs/PAL
reaction to fire	class A1
load	0,40 kN



Ing. Pavol Závodský – PULZ
 ČSL armády 388/9
 907 01 Myjava
Place of business
 Turá Lúka č.416
 Slovakia

ID: 11738286
VAT: SK1020282252

GPS:
 48.744167, 17.537133

Tel: +421 (0)34 621 61 41
Fax: +421 (0)34 621 29 91
Mob: +421 (0)949 175 845
 +421 (0)908 420 495
E-mail: pulzmyjava@pulzmyjava.sk
Web: www.pulzmyjava.sk