

Mold Resistant Dry Wall Tape

General Description

The FibaTape[®] family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers. This line includes self-adhesive fiberglass mesh tapes and corner tapes, patch and wall repair, sanding tools and accessories, ready-to-use wall patching compound and roof repair products.

Technical characteristics

Technical Characteristics		
	Warp	Weft
Setting (informative value)	36 ends / 10 cm 9 ends / in	36 ends / 10 cm 9 ends / in
Treated fabric weight (incl. glue) (informative value)	62,7 ± 2,7 g / m ² 1,85 ± 0,1 oz / yd ²	
DPU (coating + PSA) (informative value)	40 – 45 %	
Thickness (informative value)	0,3 mm 0,01 inch	
	Warp	Weft
Tensile strength	222 N / 2,54 cm 50 lbs / in	467 N / 2,54 cm 105 lbs / in
ASTM D3273 mold test	10 (Perfect)	
Dimensions & Packaging		
Standard width (1) (individual value)	48 ± 2 mm 1,6 ± 0,07 in	
Standard roll length (1) (individual value)	90 m (± 2 %) 98,43 yd (± 2 %)	
Rolls / box (1)	12	
Rolls / pallet (1)	480 (40 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) (1)	80 x 120 x 100 cm	
Quality Control		
Traceability (1)	Batch no. marked on the box	

(1) Other dimensions or features on request

Technical Data Sheet

Properties

- **Anti-mold (ASTM D3273)**
- Self-adhesive
- High mechanical strength
- Smooth finish



Edited by:
ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.
Sokolovska 106
CZ - 570 21 Litomyšl
Tel: +420 461 651 111
Fax: +420 461 612 769
www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Last update: 09/05/2012

Version: XY