

### Technical Data Sheet

#### Properties

- Specially formulated adhesive designed to excel in varying humidity levels and temperatures
- Flexibility, easy installation and cost saving

#### Technical characteristics

Characteristics	Units Description	Warp		Weft	
Setting	per 100 mm informative value	74		29	
Treated Fabric Weight, incl. glue	g/m <sup>2</sup> informative value	45 ± 2,7			
DPU (Coating and PSA)	% mass informative value	23			
Thickness	mm informative value	0,16			
Tensile strength – warp / weft	N/2,54 cm informative value	600		350	
Standard Width (1)	mm individual value	48 ± 2			
Standard Roll Length (1)	m individual value	45 or 90 ± 2 %			

(1) Other dimension on request

#### Additional Information

- **Packing:**  
A precise method of packing is mentioned in the work standard for packing.
- **Storing:**  
Packed rolls are to be stored in dry rooms. Storing temperature is from – 10 °C to + 50 °C.



Edited by:  
**ADFORS Construction Products Europe**

Saint-Gobain Vertex  
Sokolovska 106  
CZ – 570 21 Litomyšl  
Tel: + 420 461 651 111  
Fax: + 420 461 612 769  
[www.sg-adfors.com](http://www.sg-adfors.com)

**ADFORS Construction Products Europe** reserves the right to change the information given herein without prior notice

Last update: 24/05/2011