

Technical Data Sheet

General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

The FibaTape® Classic is easy to apply, ensures strong and thin joints of plasterboards and eliminates blisters and bubbles in the jointing compounds.

Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	35,4 ends / 10 cm 9 ends / in	35,4 ends / 10 cm 9 ends / in
Treated fabric weight (incl. glue) (informative value)	64,5 ± 3,5 g / m ² 1,90 ± 0,10 oz / yd ²	
DPU (PES + coating + PSA) (informative value)	41 – 47 %	
Thickness (informative value)	0,26 mm 0,01 inch	
	Warp	Weft
Tensile strength	260 N / 2,54 cm 57 lbs / inch	483 N / 2,54 cm 106 lbs / in
	Dimensions & Packaging	
Standard width ⁽¹⁾ (individual value)	48 ± 2 mm 1,89 ± 0,08 inch	
	Standard roll length ⁽¹⁾ (individual value)	
90 m (± 2 %) 98,43 yd (± 2 %)		
Rolls / box ⁽¹⁾	24	
Rolls / pallet ⁽¹⁾	480 (20 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) ⁽¹⁾	80 x 120 x 100 cm	
Quality Control		
Traceability ⁽¹⁾	Batch no. marked on the box	

Properties

- Self-adhesive
- High mechanical strength
- Smooth finish



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomyšl

Tel: + 420 461 651 111

Fax: + 420 461 612 769

www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Last update: 12.12.2017

⁽¹⁾ Other dimension or features on request