

TECHNICAL DATA SHEET OF THE PRODUCT

Quick hanger for T profile – SAH 10

Brief characteristics

The quick hanger is used as an suspension element for quick anchoring of T-profiles for the installation of a mineral ceiling into a solid building structure in a horizontal system. It is produced by pressing of galvanized sheet metal and a single-spring clamp, which is connected to the hanger by two rivets.

Technical Data:

	Quick hanger for T profile – SAH 10
thickness of material	1,3 mm
material	DX51
coating	galvanizing 100 g/m ²
	exposure class B
length	110 mm
width	20 mm
weight	0,0315 kg/pcs
small package	100 pcs
large package	16 000 pcs/PAL
reaction on fire	class A1
carrying capacity	100 N



Date: 12.6.2020



PULZ Myjava a.s.
Čsl. armády 388/9, 907 01 Myjava
IČO: 52 913 970; DIČ: 2121220827
IČ DPH: SK2121220827

PULZ Myjava a.s.
ČSL armády 388/9
907 01 Myjava
Place of business
Turá Lúka č.416, Slovensko
GPS 48.744167, 17.537133

Tel: +421 (0)34 621 61 41
Mob: +421 (0)949 175 845, +421 (0)908 420 495
E-mail: pulzmyjava@pulzmyjava.sk
Web: www.pulzmyjava.sk