

## TECHNICAL SHEET OF THE PRODUCT

### Securing clip SF1

#### Brief characteristics

The securing clip is used to couple two suspension wires in a plasterboard construction. The element allows a simple and highly variable ceiling reduction exactly as needed.

#### Technical data:

thickness of material	0,70 mm
material	DX51
coating	galvanizing 100 g/m <sup>2</sup>
	exposure class B
length	53 mm
width	27 mm
weight	0,0123 kg/pcs
small package	100 pcs
large package	10 000 pcs/PAL
reaction to fire	class A1
load	0,30 kN



**Ing. Pavol Závodský – PULZ**  
ČSL armády 388/9  
907 01 Myjava  
**Place of business**  
Turá Lúka č.416  
Slovakia

**ID:** 11738286  
**VAT:** SK1020282252  
**GPS:**  
48.744167, 17.537133

**Tel:** +421 (0)34 621 61 41  
**Fax:** +421 (0)34 621 29 91  
**Mob:** +421 (0)949 175 845  
+421 (0)908 420 495  
**E-mail:** [pulzmyjava@pulzmyjava.sk](mailto:pulzmyjava@pulzmyjava.sk)  
**Web:** [www.pulzmyjava.sk](http://www.pulzmyjava.sk)