

## DECLARATION OF PERFORMANCE No 32/SZ/16

1. Unique identification code of the product-type: **WK THERMø8**
2. Intended use/es: **Nailed-in plastic anchor for fixing of external thermal insulation composite systems with rendering in concrete and masonry**
3. Manufacturer: **Klimas Sp. z o.o.  
ul. Wincentego Witosa 135/137  
Kuźnica Kiedrzyńska 42-233 Mykanów**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **system 2+**
6. European Assessment Document: **ETAG 014 / 02.2011**  
European Technical Assessment: **ETA-11/0232 / 08.09.2016**  
Technical Assessment Body: **Instytut Techniki Budowlanej - ITB**  
Notified body/ies: **1488**
7. Declared performance/s:

Essential characteristic	Performance										
	Base material	Concrete C12/15	Concrete C16/20 - C50/60	Clay bricks MZ	Calcium silicate bricks KS	Calcium silicate hollow block KSL	Vertically perforated clay bricks HLZ	Vertically perforated clay bricks porotherm 25	Vertically perforated clay bricks MEGA-MAX		
Characteristic tension resistance	Nrk[kN]	1,2	1,5	1,5	1,5	1,2	0,6	0,6	0,6		
Edge distances and spacing	Min. allowable spacing = 100mm					Min. allowable edge distance = 100mm					
Displacement	N[kN]/δ[mm]	0,4/0,8	0,5/0,85	0,4/1,0	0,5/0,98	0,4/0,9	0,2/0,61	0,2/0,46	0,2/0,61		
Plate stiffness	[kN/mm]	0,6									
Point thermal transmittance	[W/K]	0,002									

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not applicable**

*The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*


*Signed for and on behalf of the manufacturer by:*

Kuźnica Kiedrzyńska  
18.10.2016

[place]  
[date of issue]

DORADCA TECHNICZNY

mgr inż. Adam Szczepanowski  
- 333 -



[name]  
[signature]