

## Technical Data Sheet

### General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

FibaTape® Xtreme is a self-adhesive tape made of fiberglass that can be applied in all conditions: thanks to its high tack, it performs well in winter when the temperature is low and humidity can increase during the day.

### Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	36 ends / 10 cm 9 ends / inch	36 ends / 10 cm 9 ends / inch
Treated fabric weight (incl. glue) (informative value)	(66,5 ± 3,5) g / m <sup>2</sup> (1,96 ± 0,10) oz / yd <sup>2</sup>	
DPU (PES + coating + PSA) (informative value)	43 – 48 %	
Thickness (informative value)	0,26 mm 0,01 inch	
	Warp	Weft
Tensile strength	260 N / 2,54 cm 57 lbs / inch	483 N / 2,54 cm 106 lbs / inch
	Dimensions & Packaging	
Standard width <sup>(1)</sup> (individual value)	(48 ± 2) mm (1,89 ± 0,08) inch	
	Standard roll length <sup>(1)</sup> (individual value)	
Standard roll length <sup>(1)</sup> (individual value)	90 m (± 2 %) 98,43 yd (± 2 %)	
Rolls / box <sup>(1)</sup>	12	
Rolls / pallet <sup>(1)</sup>	480 (40 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) <sup>(1)</sup>	80 x 120 x 100 cm	
Quality Control		
Traceability <sup>(1)</sup>	Batch no. marked on the box	

<sup>(1)</sup> Other dimension or features on request

### Properties

- Extreme tack
- For extreme humidity – 90 % RH
- For extreme temperature
- Self-adhesive
- High mechanical strength
- Smooth finish



Edited by:  
**ADFORS Construction Products Europe**

SAINT-GOBAIN ADFORS CZ s.r.o.  
Sokolovska 106  
CZ – 570 01 Litomyšl  
Tel: + 420 461 651 111  
Fax: + 420 461 612 769  
[www.adfors.com](http://www.adfors.com)

**ADFORS Construction Products Europe**  
reserves the right to change the  
information given herein without prior  
notice

Last update: 12.12.2017